

PRODUCT PROFILE

UNI POWER FLUSH

Superior cleaner for maintaining dampening systems

UNI POWER FLUSH works quickly to remove scum, slime, ink and paper debris from dampening fountain pans, feed lines and recirculators. Regular use in a dampening system maintenance program will prevent the build-up of slim and residues and other contaminants. This build-up can be a very serious and very expensive problem, which can ultimately shut down a press.

ADVANTAGES

- Quickly and completely removes scum, slime, ink and paper debris
- Prevents build-up of slime and residues in lines and pumps
- Regular use avoids costly downtime and lost quality

DIRECTIONS

Drain the entire press dampening system. Remove filters. Fill with fresh hot water and dilute **UNI POWER FLUSH**, 1 part in 20 parts of hot water and recirculate for 15 to 30 minutes. Flush recirculating system thoroughly with water. For tough jobs dilute 1 part of **UNI POWER FLUSH** in 10 parts of hot water and recirculate for 30 to 60 minutes. Be sure that the solution reaches all parts of the system including brushes or spray nozzles.

Safety data sheet available upon request

Code 305



51, BEAUVAIS STREET, DELSON (QUEBEC) CANADA J5B 1W5, TEL.: (450) 632-5871 ■ FAX: (800) 366-8812 ■ TECH. ASSIST.: (800) 996-9918
www.unigraphinternational.com ■ service@unigraphinternational.com

