

PRODUCT PROFILE

UNI FOUNT SM 553 K

For Small Offset Presses and Duplicators

Uni Fount SM 553 K provides high print quality on polyester, paper photo-direct plates, and on all types of metal offset plates (except electrostatic). **Uni Fount SM 553 K** will perform exceptionally well on all rubber-based and oil-based inks.

Uni Fount SM 553 K runs equally well on a wide variety of dampening systems as conventional, integrate, Kompac and Cresline. Its balanced formulation keeps non-image areas highly hydrophilic, while image areas remain highly ink receptive.

FEATURES & BENEFITS

- Compatible with all plates
- Efficient with all types of ink (rubber-based and oil-based)
- pH or conductivity is not a concern
- Glycerin-based

DIRECTIONS

For presensitized and additive metal plates, camera and photo-direct plates:
From 6 up to 20 parts water to 1 part **Uni Fount SM 553 K**.

For paper masters, direct image and diffusion transfer plates:
From 6 up to 24 parts water to 1 part **Uni Fount SM 553 K**.

Use full strength as pre-wetting agent on paper masters.

TECHNICAL DATA

VOC (lbs/gal.): 1.68
VOC (g/l): 201
Flash Point: 110°F (43°C)
Glycerin-based

Sheetfed

Small & Medium
Presses

PACKAGING

CANADA
4 X 4 Liter
20 Liter Pail

USA
4 X 1 Gallon
5 Gallon Pail

Safety data sheet available upon request

Code 553



51 BEAUVAIS STREET, DELSON (QUEBEC) CANADA J5B 1W5, TEL.: (450) 632-5871 ■ FAX: (800) 366-8812 ■ TECHNICAL ASSISTANCE: (800) 996-9918
www.unigraphinternational.com ■ service@unigraphinternational.com

