PRODUCT PROFILE



UNI SILICONE ANTI-MARKING EMULSION 60A is a unique concentrated formula incorporating silicone, antismear agents, anti-static material and other ingredients. This combination of silicone and non-hazardous trade secret materials provides better slip, prevents ink smearing, eliminates static electricity. Can be used on any type of heatset or coldset presses and on different types of paper or board.

ADVANTAGES:

- · Prevents ink smearing and offset
- · Provides smooth delivery in folder or sheeter
- · Dries faster in the stock than other silicone emulsions
- · Controls static during all operations
- Contains anticorrosive agents preventing corrosion of metal parts
- · Incorporated biocide protects diluted solution from bacteria and fungi
- · Very economical
- · Eliminates cracking of paper on folder
- · Exceptional slip qualities, works better and more economical than pure silicone
- · Prevents static build up on printed sheet
- · Eliminates deposits on rollers
- No VOC content

DIRECTIONS:

UNI SILICONE ANTI-MARKING EMULSION 60A recommended dosage: 2 to 6 ounces per gallon of water. For best results, use proportioner pump such as the Dosatron Graphic D14MZ10 doser. This insures a consistent dilution and prevents excessive use of emulsion. No additives like anti-stat etc. are necessary for 60A emulsion.

Safety data sheet available upon request **Code 720**



51 BEAUVAIS, DELSON (QUEBEC) CANADA J5B 1W5 | T 450-632-5871 | 800-996-9918 | F 800-366-8812 www.unigraphinternational.com | service@unigraphinternational.com











